

TECHNICAL DATA

SOFT POLYESTER FABRIC UNTREATED

DESCRIPTION:

- A unique, 100% warp knit polyester fabric.
- Excellent tensile strength provides tear and puncture resistance.
- Compatible cold (liquid) applied bitumen systems and water-based elastomeric coatings.
- Outstanding conformability and elongation properties.
- Superior wetting properties, lightweight and dimensionally stable.
- Will not rot, mold or mildew.

APPLICATION:

- Apply a film of the cold (liquid) applied bitumen adhesive to the surface, in accordance with the manufacturer's recommendations.
- Embed Fortress Soft Polyester Fabric into the adhesive using a brush or broom and enough pressure to force the adhesive through the mesh openings and around the fabric strands.
- Conform the fabric uniformly to the surface, avoiding over-stretching, bridging or "fishmouths".
- Apply a final coat of the cold (liquid) applied bitumen adhesive to the surface, in accordance with the manufacturer's recommendations, ensuring that no fabric weave is visible.

Property	Result
Weight, oz./sq. yd.	2.7
Tensile Strength, lb./in.	75
Tear Strength, lb./in.	13.5
Elongation to break, %	42.9
Color	white

PACKAGING:

- Available in 300 feet lengths and 42 inch cut widths. Other cut widths also available. Consult price sheet for additional details.

SPECIFICATION COMPLIANCES:

- Meets normal industry standards

SAFETY AND ENVIRONMENTAL PRECAUTIONS:

- **CONSULT MATERIAL DATA SAFETY SHEET FOR DETAILED HANDLING AND DISPOSAL**